

PROTECTION YOU CAN AFFORD FOR THE RECORDS YOU CAN'T AFFORD TO LOSE.

Protect your business with a FireKing® Data Safe.



FireKing® 

The best records protection you can buy.

FIREKING 3-HOUR DATA SAFE

CAPACITY GUIDE

Media Type	DM1413-3	DM2513-3	DM2520-3	DM3420-3	DM4420-3
3.5" Diskettes					
Quantity per Drawer	306	306	536	536	536
Number of Fittings	3	6	6	8	10
3480 IBM Cartridges					
Quantity per Drawer	28	28	51	51	51
Number of Fittings	2	4	4	6	8
4mm DAT Tapes					
Quantity per Drawer	70	70	125	125	125
Number of Fittings	4	7	7	10	13
8mm-DAT Tapes					
Quantity per Drawer	39	39	72	72	72
Number of Fittings	4	7	7	10	13
CD ROM					
Quantity per Drawer	70	70	123	123	123
Number of Fittings	2	4	4	5	7
DLT Tapes					
Quantity per Drawer	24	24	42	42	42
Number of Fittings	2	5	5	6	8
ZIP® PC 100					
Quantity per Drawer	73	73	128	128	128
Number of Fittings	3	5	5	7	9

Capacity guides are based on average media sizes.

TEST PROCEDURE

*Maintain an interior temperature less than 125°F and an interior relative humidity less than 80% for class 125, when exposed to fire as per the Standard Time Temperature Curve for 3 hours to 1925°. Successfully undergo all other requirements for the Fire Endurance Test, the Explosion Hazard Test, the Humidity Test and the Fire and Impact Test.

OPTIONAL INTERIORS

CM12-FS Fixed shelf for DM1413/DM2513
 CM12-CD Composite Drawer for DM1413/DM2513
 CM19-FS Fixed shelf for DM2520/DM3420/DM4420
 CM19-CD Composite Drawer for DM2520/DM3420/DM4420

Safe shown with optional interiors sold separately.

SPECIFICATIONS


FIREKING 3-HOUR FIRE WITH IMPACT-RATED DATA SAFES

Model	Interior Size			Exterior Size			Weight	Capacity
	H	W	D	H	W	D		
DM1413-3	13 ⁵ / ₈ "	11 ¹ / ₂ "	16 ¹¹ / ₁₆ "	29 ⁵ / ₈ "	25 ¹ / ₄ "	31"	650 lbs.	1.5 cu. ft.
DM2513-3	24 ⁵ / ₁₆ "	11 ¹ / ₂ "	16 ¹¹ / ₁₆ "	40 ¹ / ₄ "	25 ¹ / ₄ "	31"	740 lbs.	2.7 cu. ft.
DM2520-3	24 ¹⁵ / ₁₆ "	18 ⁵ / ₈ "	16 ¹¹ / ₁₆ "	40 ¹ / ₄ "	32 ¹ / ₁₆ "	31"	1,050 lbs.	4.4 cu. ft.
DM3420-3	33 ¹ / ₈ "	18 ⁵ / ₈ "	16 ¹¹ / ₁₆ "	49 ¹ / ₁₆ "	32 ¹ / ₁₆ "	31"	1,240 lbs.	6.0 cu. ft.
DM4420-3	43 ⁵ / ₈ "	18 ⁵ / ₈ "	16 ¹¹ / ₁₆ "	59 ³ / ₄ "	32 ¹ / ₁₆ "	31"	1,420 lbs.	7.9 cu. ft.

Exterior depth does not include handle
 Handle depth is 1-3/4"

FEATURES

- Programmable electronic lock for security and easy access
- Safe is offered in our attractive Platinum finish
- UL RSC Burglary Rating
- UL Class 125 3-Hour fire and impact rating
- Canadian UL Class 52 3-Hour as to fire and impact resistance



FIREKING 3-HOUR FIRE WITH IMPACT-RATED DATA SAFES

The FireKing 3-Hour Fire With Impact-Rated Data Safes provide the ultimate in protection against fire, dust, electrostatics and accidental damage for your computer media. They're our highest rated safes and are perfect for businesses with large-capacity electronic storage needs. FireKing 3-Hour Data Safes are available in five sizes, all featuring the UL Class 125 3-hour fire and impact rating*, plus the UL Residential Security Container (RSC) Burglary Rating for tough protection against break-in.

FIREKING 2-HOUR DATA SAFE



CAPACITY GUIDE

Media Type	DS2320	DS3420	DS4520	DS6431	DS6431
3.5" Diskettes					
Quantity per Drawer	608	608	608	608	1150
Number of Fittings	5	8	11	16	16
3480 IBM Cartridges					
Quantity per Drawer	51	51	51	51	99
Number of Fittings	4	7	9	13	13
4mm DAT Tapes					
Quantity per Drawer	120	120	120	120	239
Number of Fittings	9	14	18	26	26
8mm DAT Tapes					
Quantity per Drawer	79	79	79	79	154
Number of Fittings	7	10	14	20	20
CD ROM					
Quantity per Drawer	117	117	117	117	225
Number of Fittings	4	6	8	11	11
DLT Tapes					
Quantity per Drawer	48	48	48	48	94
Number of Fittings	4	7	9	11	11
ZIP® Disk					
Quantity per Drawer	128	128	128	128	254
Number of Fittings	5	7	10	14	14

Capacity guides are based on average media sizes.

OPTIONAL INTERIORS

CS20-FS	Fixed shelf for DS2320/3420/4520/6420-2
CS20-CD	Composite drawer for DS2320/3420/4520/6420-2
CS31-FS	Fixed shelf for DS6431-2
CS31-CD	Composite drawer for DS6431-2

TEST PROCEDURE

*Maintain an interior temperature less than 125°F and an interior relative humidity less than 80% for class 125, when exposed to fire as per the Standard Time Temperature Curve for 2 hours to 1850°F. Successfully undergo all other requirements for the Fire Endurance Test, the Explosion Hazard Test, the Humidity Test and the Fire and Impact Test.

Safe shown with optional interiors sold separately.

SPECIFICATIONS

FIREKING 2-HOUR FIRE WITH IMPACT-RATED DATA SAFES

Model	Interior Size			Exterior Size			Weight	Capacity
	H	W	D	H	W	D		
DS2320-2	22½"	19⅝"	15⅜"	36⅞"	29⅞"	30"	680 lbs.	4.04 cu. ft.
DS3420-2	33⅞"	19⅝"	15⅜"	47⅜"	29⅞"	30"	880 lbs.	5.41 cu. ft.
DS4520-2	44⅞"	19⅝"	15⅜"	58⅞"	29⅞"	30"	1,070 lbs.	8.07 cu. ft.
DS6420-2	63⅞"	19⅝"	15⅜"	76⅜"	29⅞"	30"	1,380 lbs.	10.78 cu. ft.
DS6431-2	63⅞"	30¾"	18⅞"	76⅜"	40⅞"	32⅞"	1,870 lbs.	20.6 cu. ft.


See your dealer for the complete selection of interior designs.

FIREKING 2-HOUR FIRE WITH IMPACT-RATED DATA SAFES

The FireKing 2-Hour Fire With Impact-Rated Data Safe provides an ideal way to store all types of magnetic media and protects them against fire, dust and accidental damage. They are available in five sizes to accommodate your storage needs. These affordable safes provide the ultimate in protection by incorporating layers of heat-absorbing material, fireproof insulating foam and fireproofing with a tough steel casing. Three-way boltwork ensures that doors remain shut if a building collapses during a fire or if a forced entry is attempted. Each FireKing 2-Hour Data safe carries a UL Class 125 2-hour fire and impact rating*.

FEATURES:

- Programmable electronic lock for security and easy access
- Safe is offered in our attractive light gray color (RAL9002)
- Optional interiors allow various configurations to meet your storage needs



FIREKING 1-HOUR DATA SAFE



TEST PROCEDURE

*Maintain an interior temperature less than 125°F and an interior relative humidity less than 80% for class 125, when exposed to fire as per the Standard Time Temperature Curve for 1 hour to 1700°F. Successfully undergo all other requirements for the Fire Endurance Test, the Explosion Hazard Test, the Humidity Test and the Fire and Impact Test.

Safe shown with optional interiors sold separately.

CAPACITY GUIDE

Media Type	DS1513-LG	DS1817-LG
3.5" Diskettes		
Quantity per Drawer	264	480
Number of Fittings	3	4
4mm DAT Tapes		
Quantity per Drawer	60	108
Number of Fittings	3	4
8mm DAT Tapes		
Quantity per Drawer	32	63
Number of Fittings	3	4
CD ROM		
Quantity per Drawer	58	108
Number of Fittings	2	3
DLT Tapes		
Quantity per Drawer	18	39
Number of Fittings	3	3
ZIP® PC 100		
Quantity per Drawer	58	111
Number of Fittings	3	4

Capacity guides are based on average media sizes.

OPTIONAL INTERIORS

CS12-FS	Fixed shelf for DS15130-1
CS12-CD	Composite drawer for DS1513-1
CS16-FS	Fixed shelf for DS1817-1
CS16-CD	Composite drawer for DS1817-1

SPECIFICATIONS

FIREKING 1-HOUR FIRE WITH IMPACT-RATED DATA SAFES

Model	Interior Size			Exterior Size			Weight	Capacity
	H	W	D	H	W	D		
DS1513-1LG	14 ³ / ₈ "	12 ⁷ / ₁₀ "	12 ⁷ / ₁₀ "	25 ¹ / ₂ "	21 ¹ / ₂ "	22 ² / ₅ "	297 lbs.	1.3 cu. ft.
DS1817-1LG	17 ¹ / ₈ "	16 ³ / ₈ "	17"	28 ³ / ₈ "	25 ¹ / ₂ "	26 ³ / ₈ "	429 lbs.	2.8 cu. ft.

FIREKING 1-HOUR FIRE WITH IMPACT-RATED DATA SAFES

The FireKing 1-Hour Fire With Impact-Rated Data Safe has a wide range of interiors for storing magnetic media, making it a versatile and economical choice. Computer media is easily damaged. Manufacturers recommend storing magnetic media at a temperature below 125°F and at a humidity level under 80%. Even a hot mug of coffee represents a real hazard, so imagine what a fire would do. In a FireKing Data Safe, computer media is protected from fire, dust, magnetic fields, unauthorized access, accidental damage and electrostatics. The 1-Hour Data Safe comes in two convenient sizes, DS1513 and DS1817, and both carry a UL Class 125 1-hour fire and impact rating*.

FEATURES:

- Equipped with a high-security key lock
- Safe is offered in our attractive light gray color (RAL9002)



FIREKING MEDIAVAULT™



FireKing 1-Hour UL Class 125 Fire Rating.

FIREKING MIXED MEDIA SAFE



Safe shown with optional interiors sold separately.



**MEDIA COMPARTMENT
OPTIONAL INTERIORS**
CM19-FS Fixed shelf
CM19-CD Composite drawer

**PAPER COMPARTMENT
OPTIONAL INTERIORS**
S-21 Fixed shelf

CAPACITY GUIDE

Media Type	MV1000	DP2150-M
3.5" Diskettes	130	536
4mm DAT	60	125
8mm DAT	30	72
CD-ROM	23	123
DLT	12*	42
3480/3590	9	51
Zip disk 100	31	128

*Without plastic sleeves.

SPECIFICATIONS

Model	Interior Size			Exterior Size			Weight	Capacity
	H	W	D	H	W	D		
MV1000	5 ⁷ / ₈ "	6 ¹ / ₄ "	8 ⁵ / ₈ "	10 ¹ / ₂ "	11 ⁵ / ₈ "	17 ¹ / ₂ "	74 lbs.	
DP2150-M				59 ³ / ₄ "	32 ¹ / ₈ "	31"	1,290 lbs.	
Paper compartment	19 ¹ / ₂ "	26 ³ / ₄ "	20 ²⁹ / ₃₂ "					6.1 cu. ft.
Media compartment	24 ⁵ / ₁₆ "	18 ⁵ / ₈ "	16 ¹¹ / ₁₆ "					4.4 cu. ft.

*Exterior depth does not include handle.
Handle depth is 1³/₄"

FIREKING MEDIA VAULT™



FIREKING
MIXED MEDIA SAFE

THE COMPACT, STAND-ALONE
FIREKING® MEDIAVAULT PROVIDES
SECURITY, CONVENIENCE AND PEACE OF MIND.

The MediaVault is the only compact and affordable media safe of its size designed to meet Underwriters Laboratories (UL) Class 125, one-hour specification for insulated record protection equipment. This specification ensures that the interior temperature of the storage device does not exceed 125°F when exposed to a fire of 1700°F for a period of one hour and during that time the interior relative humidity does not exceed 85%RH. Whether it's microfiche, photographs or computer data on virtually any standard media (see chart above), the MediaVault will protect it from dust and fires of up to 1700°F. The MediaVault is equipped with a key lock conveniently located on the lid for added security.

FIREKING MIXED MEDIA SAFE

The Mixed Media Safe from FireKing offers the ultimate in versatile protection – because it's really two safes in one. The top section is a UL® Class 350 1-Hour Impact Rated safe with over 6 cubic feet of storage for your important paper records and files. The bottom is a UL Class 125 3-Hour Impact Rated data media compartment to hold your CDs, tapes, discs and other media.





THINK ABOUT IT.

Losing your important recorded data to a fire is not bad luck, it's bad business! Protect your valuable computer media with one of FireKing's affordable, UL-rated data safes. From our compact, stand-alone MediaVault to our large-capacity 1-hour, 2-hour, and 3-hour dual-rated data safes, FireKing offers a safe to fit your needs.



FireKing® International, Inc.
101 Security Parkway
New Albany, Indiana 47150

812-948-8400/800-457-2424 • Fax: 812-948-0437/800-227-7513
E-mail: fireking@fireking.com • website: www.fireking.com



FireKing International, Inc.
is ISO 9001:2000 Certified

Underwriters Laboratories, Inc.* and UL*
are registered trademarks of Underwriters
Laboratories and are used with permission.